

Mini Cabinet




There are two types:

- Vertical laminar flow cabinet BBS-V500: positive pressure in work area only protects sample.


Air Flow Pattern:

BBS-V500



- Class I biological safety cabinet BYKG-VII: negative pressure in work area protects operator and environment.

BYKG-VII



ADVANTAGE

1. Air speed adjustable.
2. Tabletop type, easy to carry and save space.
3. Microprocessor control system, LED Display.
4. HEPA Filter with efficiency: 99.999% at 0.3µm.

TECHNICAL PARAMETERS

Model	BBS-V500	BYKG-VII
External Size (W*D*H)	550*460*700mm	
Internal Size (W*D*H)	480*340*370mm	
Display	LED Display	
Airflow Velocity	0.3~0.5m/s	≥0.5m/s
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3µm	
Noise	<80dB	
Front Window	Manual, 5mm toughened glass, anti UV	
Max Opening	310mm	
Fluorescent Lamp	8W*1	
UV Lamp	8W*1	8W*1
	Emission of 253.7 nanometers	
Consumption	100W	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	Fluorescent lamp*1, UV lamp*2	
Gross Weight	57kg	63kg
Package Size (W*D*H)	700*510*830mm	700*510*830mm

